

GESS-SW-1500TH-POB

1.5MW/1.553MWh (1C)



GESS

**Swedish Grid approved PCS with
EN50549 , EIFS 2018:2 certification**



**BESS DESIGNED BY
SWEDISH ENGINEERS**

Global Energy Storage Solutions Battery AB

Helgenäsvägen 37 , 594 75 Edsbruk, Sweden. | +46 769 411422 | www.gess.se | info@gess.se

Features

- 1.5MW/1.553MWh capacity Forced Air-cooled (1CP)
- Swedish Grid approved PCS with EN50549 & IEC 6218:2 certification
- Cold start operations from -20°C
- Fully containerized IP55 system.
- Specially designed for FFR market with less than 600ms response time
- Can be used for other BESS applications (Reactive power trading, Peak shaving, UPS etc.)
- LiFePO4 Battery technology
- Backup power unit for emergency internal usage
- Directly communicating with IEC60870-5-104 /101, Modbus TCP
- 3 years warranty for PCS
- Cell cycle life: 4000 cycles or 5 years

CELL Standard:

- IEC 62619
- UL 1973
- UL9540A
- UN 38.3

Pack Standard:

- IEC 62619
- UL9540A

System Standards :

- IEC 62619

PCS Standards :

- IEC62477
- EN61000
- EN50549
- IEC 6218:2

Technical specification	GESS-SW-1500TH-POB
Maximum discharge power (kW)	1650
Maximum 2Sec discharge power (kW)	1800
Name plate capacity (kWh)	1500
Rated capacity (kWh)	1553
Dimensions	2 nos 20Ft containers connecting together at the site
Weight (T)	<31 T
Cell parameters	
Cell type	LFP
Rated capacity (Ah)	120 (123--125)
Rated voltage (V)	3.2
Rated energy (kWh)	0.384 (+0.3936--0.4)
Voltage range (V)	2.0-3.65
Charging cut-off voltage (V)	3.6
Discharge cut-off voltage (V)	2.8
Operating humidity	< 85% ROH, no condensation
Discharge Power Efficiency	97%
Calendar life	not less than 10 years
Battery pack parameters	
Combination	1P24S
Rated capacity (Ah)	120
Rated voltage (V)	76.8
Capacity (kWh)	9.216 (9.446-9.6)
Fire Fighting system	
Perfluorohexanone fire protection system	2 set
Cooling system	
Forced air cooling system with six air conditioner units	2 set

PCS parameters	
PCS systems	3
Nominal power	500kVA
AC max power	550kVA
AC frequency	50/60(-2.5~2.5) Hz
AC voltage	400(-15%~15%) Vac
Battery voltage range	600~900Vdc
Quantity of battery strings	8
DC max current in each branch	110A
THDi	≤ 3%
AC PF	Listed: 0.8~1 leading or lagging (Controllable) Actual: 0.1~1 leading or lagging (Controllable)
Cooling	Forced air cooling
Noise	<75d B
Enclosure	NEMA1 IP20 and optional IP54 with outdoor cabinet
Max elevation	3000m/ 10000feet (> 3000m/ 10000feet derating)
Operating ambient temperature	(-20°C to -55°C*) to 50°C (Derating over 45°C)
Humidity	0~95% (No condensing)
Size (W × H × D)	1100×2160×800 mm
Weight	Cabinet 280kg + Module 40kg*n (n=1, 2, ..., 8)
Installation	Floor standing OTP, AC OVP/ UVP, OFP/ UFP, EPO, AC Phase Reverse, Fan/ Relay Failure, OLP, GFDI, Anti-islanding
Protection	Upper/ Lower AC Voltage/ Frequency limit, Battery EOD voltage
Configurable protection limits	
AC connection	3-Phase 3-Wire
Display	Touch Screen
Communication	RS485, CAN, Ethernet
Isolation	Non-isolation
Certification	CE LVD IEC 62477, CE EMC IEC 61000, EN 50549-1:2019 G99, AS4777

*Optional features * Specification can be changed without notice